


Product image			Features
			★ F2.0 large aperture, more light intake, clearer night vision
			★ Remote access, two way audio
			★ ISP image processing technology, preserving true colors
			★ Human detection, real time alerts
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.27-inch 1080p progressive scanning CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision
3	Video	Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP (Interpolation)
		Night vision	20-30 meters
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression	G711A
5	Pan/Tilt	Rotation angle	N/A
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage(purchased separately)
8	Alarm	Alarm detection	Motion detection, human detection, human framing, and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 3.96W (0.33A) Maximum power: 6.36W (0.53A)
		Operating condition	Working temperature: -10 ~ 55°C, working humidity <90%
		Weight	N.W. : 300g ; G.W. : 600g
		Camera size	183x71x73mm
		Packaging box size	228x149x93mm
		Carton size	490x470x320mm, 20PCS/Carton