



Hewlett Packard
Enterprise

HPE OFFICECONNECT 1950 48G 2SFP+ 2XGT SWITCH (JG961A)

**Fixed Port Web Managed Ethernet
Switches**



WHAT'S NEW

- Flexible 10GbE connections-10GBASE-T copper and SFP+ fiber-in an affordable, smart web-managed switch series.
- Four-high stacking can simplify network administration and add resiliency.
- Power over Ethernet models supporting up to 370 Watts total PoE+/PoE power.
- Customized operation using intuitive Web

OVERVIEW

The HPE 1950 Switch Series is a family of smart web-managed Gigabit switches with 10GbE uplinks for small business customers needing advanced high-performance connections. The series has 2 standard and 2 PoE+ models, 24- and 48-GbE ports, each with 2 10GBASE-T and 2 10G SFP+ high-bandwidth ports.

True stacking of as many as 4 devices allows them to be logically administered as a single entity. The switches support

browser-based interface

- Limited lifetime warranty for unit, power, and fans.

Layer 3 static routing on IPv4 and IPv6. Other advanced features include ACLs, 802.1X, STP, RSTP, and MSTP. Limited lifetime warranty covers unit, fans and power supplies.

FEATURES

High-level Gigabit with 10GbE Networking for Advanced Small Businesses.

Each model of the HPE 1950 Switch Series includes four 10GbE connections to connect to servers, network storage devices, or to other switches.

Two connections of 10GBASE-T deliver 10GbE over copper Category 6a cabling for simple, affordable, high-bandwidth connections to a maximum distance of 100 meters.

Two SFP+ ports allow for fiber connectivity at various distances, at 1/10GbE speeds, using optional SFP+ 10GbE or SFP Gigabit transceivers.

Aggregate 10GbE connections for even higher bandwidth using Link Aggregation Control Protocol.

Simplified Network Administration

Logically group or "stack" as many as four units of the HPE 1950 Switch Series and manage this as a single entity, greatly simplifying network administration. Interconnect stacked units using 10GbE connections, with as much as 40GbE total stacking bandwidth connecting the units.

Use the intuitive web-browser based interface to configure and administer these smart-managed devices.

These devices support SNMP versions 1, 2c and 3, allowing administration of these devices from a remote SNMP-based management platform.

Network Time Protocol facilitates timekeeping across your network so time-based actions and trouble-shooting logs are kept synchronized.

Units will automatically retrieve an IP Address from a DHCP server, allowing for near plug-and-play deployments.

Robust Security to Protect Your Network

The HPE 1950 Switch Series lets you use Virtual LANs and access control lists to set bounds on what data can be seen by which users.

Leverage 802.1X with a RADIUS server to ensure only known and authorized users can access your network.

Multiple features guard your network from user or server spoofing and from malicious network-based attacks.

Help secure management traffic using supported SSL/HTTPS encryption and SNMPv3 capabilities.

Resiliency Features to Keep Your Network Running

The HPE 1950 Switch Series supports Spanning Tree Protocol, Rapid Spanning Tree Protocol, and Multiple Spanning Tree Protocol standards for creating hot-standby recovery links.

Distribute important links across multiple units in a logical stack for added



resiliency. Units can even be in different buildings and still be logically stacked.

Devices support two independent primary and secondary operating system flash images for backup and recovery during unit upgrades.

Power over Ethernet (PoE) models can be paired with an optional Redundant Power System which can maintain power even if the unit's power supply fails, as well as supplement available PoE power up to 780 Watts.

Technical specifications

HPE OfficeConnect 1950 48G 2SFP+ 2XGT Switch

Product Number (SKU)	JG961A
Differentiator	Advanced smart web managed 48-port Gigabit switch with 10G uplinks. This model has 48x 10/100/1000 ports plus two 10GBASE T copper ports and two SFP+ ports for SFP+/SFP fiber connections.
Ports	(48) RJ-45 auto-negotiating 10/100/1000 ports (2) SFP+ fixed 1000/10000 SFP+ ports (2) RJ-45 1/10GBASE-T ports
Memory and processor	128 MB flash Packet buffer size: 3 MB 1 GB SDRAM
Latency	100 Mb Latency: < 5 μ s 1000 Mb Latency: < 5 μ s 10 Gbps Latency: < 1.5 μ s
Throughput	up to 130.9 Mpps
Routing/switching capacity	176 Gbps
Stacking capabilities	Virtual 4 switches
Management features	IMC - Intelligent Management Center Limited command-line interface Web browser SNMP manager HTTPS RMON1 FTP Supported by HPE IMC and generic SNMP management platforms. Refer to documentation for MIB support details.
Input voltage	100 - 240 VAC, rated (depending on power supply chosen)
Operating humidity range	10 to 90% (noncondensing)
Power Consumption	54 W (maximum)
Minimum dimensions (H x W x D)	44 x 27 x 4.4 cm
Weight	5 kg



For additional technical information, available models and options, please reference the [QuickSpecs](#)

HPE POINTNEXT

Access expertise at every step of your IT journey with [HPE Pointnext Services](#). [Advisory Services](#) focuses on your business outcomes and goals, to design your transformation and build a roadmap tuned to your unique challenges. Our [Professional](#) and [Operational Services](#) help speed up time-to-production and keep your IT stable and reliable.

Operational Services from HPE Pointnext Services

- [HPE Datacenter Care](#) helps modernize and simplify IT operations. Partner with an assigned account team, access technical expertise, an enhanced call experience gives you priority access, choose hardware and software support, implement proactive monitoring to help stay ahead of issues, and access HPE IT best practices and IP.
- [HPE Proactive Care](#) offers an enhanced call experience and helps reduce problems with personalized proactive reports and advice. This also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.). [Read more](#)
- [HPE Foundation Care](#) helps when there is a problem and has a choice of response levels. Collaborative software support is included and provides troubleshooting help for ISVs running on your server. [Read more.](#)

Other related services

[Defective Media Retention](#) is optional and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

[HPE Service Credits](#) offers a menu of technical services, access additional resources, and specialist skills.

[HPE Education Services](#) provides comprehensive training designed to expand the skills of your IT staff and keep them up to speed with the latest technologies.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options.



HPE GREENLAKE

[HPE Greenlake](#) is HPE's market-leading IT as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model. HPE GreenLake delivers public cloud services and infrastructure for workloads on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

**Make the right purchase decision.
Contact our presales specialists.**

[Find a partner](#)



**Hewlett Packard
Enterprise**

© Copyright 2020 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product
[PSN6887557ILEN](#), July 01, 2020.