

Condensed Aerosol generators

FP-80S 	TECHNICAL INFORMATION	
	Model	FP-80S
	Activation mechanism	electrical (min.1.5V DC, min 0.8A in 3-4 sec)
	Activator type	heating element with 2.3 ohm resistance
	Activ. line supervision current	maximum 5 mA
	Weight gross	870 g
	Mass of FPC Compound	80 g
	Operational discharge time	5 - 10 seconds
	Discharge outlets	2
	Discharge length	2 m
	Size	185 mm x 51 mm (incl. connector housing)
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
	Cabinets	electrical cabinets
	Instrumentation	mechanical machines
	Switch boxes (medium)	relay boxes, meter cupboards
	Transformers (medium)	(small) portable welders
		Certified according to EN 15276-1, BRL 23001 and ISO 15779

FP-80T 	TECHNICAL INFORMATION	
	Model	FP-80T
	Activation mechanism	thermal activation electrical (min.1.5V DC, min 0.8A in 3-4 sec)
	Activator type	heating element with 2.3 ohm resistance
	Activ. line supervision current	maximum 5 mA
	Weight gross	870 g
	Mass of FPC Compound	80 g
	Operational discharge time	5 - 10 seconds
	Discharge outlets	1
	Discharge length	2 m
	Size	185 mm x 51 mm (incl. connector housing)
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
	Cabinets	electrical cabinets
	Instrumentation	mechanical machines
	Switch boxes (medium)	relay boxes, meter cupboards
	Transformers (medium)	(small) portable welders
		Certified according to EN 15276-1, BRL 23001 and ISO 15779

