

Reolink-Lumus-IP-Camera-Specifications			
	Model	Reolink Lumus	
Video & Audio	Image Sensor	1/2.8" CMOS Sensor	
	Video Resolution	1920 x 1080 (2.0 Megapixels) at 15 FPS	
	Lens	f=2.8mm, F=2.2, with IR Cut	
	Video Format	H.264	
	Field of View	Horizontal:	100°
		Vertical:	54°
	Day & Night	Auto-switching with IR-cut filter	
	Night Vision Distance	10m (33ft) (LED: 6pcs/14mil/850nm)	
Smart Alerts	Audio	Two-way audio	
	Mode	PIR + Motion detection	
	PIR Detecting Distance	Up to 7m (21ft); Adjustable	
	PIR Detecting Angle	Horizontal: 100°	
	Alert	Instant email alerts, push notifications, siren (customizable)	
Hardware Features	Power	DC 5.0V/2A, <6W	
	Spotlight	1.6W, 6500K, 180lm	
	Interface	Micro SD Card Slot (support up to 128GB micro SD card)	
		Built-in Microphone and Speaker	
Software Features	Mainstream	Resolution: 1920 x 1080	
		Frame rate: 2 ~ 15 FPS (default: 15 FPS)	
		Code rate: 512kbps ~ 2048kbps (default: 2048kbps)	
	Substream	Resolution: 720 x 576	
		Frame rate: 4 ~ 15 FPS (default: 10 FPS) Code rate: 128kbps ~ 768kbps (default: 384kbps)	
	Browser Supported	No	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion-triggered recording; scheduled recording	
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, DHCP, DNS, DDNS, P2P	
Maximal User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)		
Work with	Google Assistant, Reolink Cloud (available in some countries)		
WiFi	Wireless Standard	IEEE 802.11 b/g/n	
	Operating Frequency	2.4 GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Working Environment	Temperature	Operating Temperature: -10°C ~ 55°C	
		Storage Temperature: -40°C ~ 70°C	
	Humidity	Operating Humidity: 20% ~ 85%	
		Storage Humidity: 10% ~ 90%	
Waterproof	IP65		
Size & Weight	Dimension	99 x 91 x 60mm	
	Weight	185g	
Warranty	Limited warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>	