

RLC-423-Refurbished-IP-Camera-Specifications		
	Model	RLC-423 (Refurbished)
Video & Audio	Video Resolution	Default: 5.0 Megapixels
	Video Format	H.264
	Angle of View	Horizontal: 87°~31°, Vertical: 65°~24°
	Day/Night Mode	Auto-switching with IR-cut filter
	Min. Illumination	0 Lux (with IR Illuminator)
	Infrared Night Vision	60 meters (190ft)
	Optical Zoom	4X
Power	POE	IEEE 802.3at, 48V active
	DC Power	DC 12.0V=2A, <20W
Interface	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps; RJ45
	Audio	Microphone connector (an extra microphone is required for audio recording)
Pan&Tilt	Pan &Tilt Range	Pan: 360°, Tilt: 0°~90°
	Pan Speed	2.5°-180°/s (Speed can be set)
	Tilt Speed	1.5°-90°/s (Speed can be set)
	Preset	64
	Patrol	1 Patrol; up to 16 presets per patrol
	Power Memory	Support
Software Features	Frame Rate	Up to 25fps
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Alarm	Motion detection
	Record Mode	Motion recording
	Max. User Access	20 users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
Working Environment	Temperature	Operating temperature: -10°C ~ +55°C (14°F~131°F)
	Humidity	Operating humidity: 20% ~ 85%
Size & Weight	Dimensions	Φ136 x 201mm
	Weight	1.60kg
Warranty	Limited Warranty	1-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .