

Product description

The basic public address 5 zone mixer amplifiers has power 240W. It is featured of 3 microphone inputs, 2 aux inputs and 1 EMC input. Priority muting is achieved via EMC for overriding other inputs except Mic1 on front panel.

Individual gain controls are provided for Mic 1-3 and Aux 1-2, bass and treble controls and master volume control are provided for overall tone control. 70V, 100V and low impedance 4-16ohms speaker outputs are provided. Extensive protection from short-circuit, overload and high temp.

Features

- * Mixer amplifier for paging and background music system
- * Rated power 240W
- * 2U rack mount
- * 70V, 100V and low impedance 4-16ohm speaker output
- * 5 zone and all zone speaker terminals
- * Three Mic inputs by phone jack type
- * Mic 1 with VOX priority and VOX level on front panel
- * Mic 2-3 by phone jack on rear panel
- * Two Aux Inputs and 2 line inputs for spare use
- * One EMC priority input
- * EMC has priority over all inputs except MIC1
- * Mic 1-3, Aux 1-2 and master volume controls and bass/treble tone control
- * Short circuit, overload and high temp protection

Technical data

Power Supply	220-240V
Rated Power Output	240W
Outputs	4Ω, 70V, 100V
Frequency Response	50Hz - 15 kHz
THD	less than 1%
S/N	MIC: 66dB; AUX: 80dB
Dimensions	19"/3U
Weight	15kg