

64CH NVR

NVR5-641600(2U)



8MP



| MODEL | NVR5-641600 (2U) | |
|--------------------|-----------------------------|--|
| Video | Input | 64CH over Network |
| | Output | HDMI1 (4K, 1080P/1280x1024), HDMI2 + VGA (1280x1024, 1080P), 32Ch per Monitor |
| | Decoding Format | H.265 / H.264 |
| | Decoding Capabilities | 1Ch - 8MP ; 4Ch - 2x8MP + 2x5MP ; 9/16Ch - 1MP ; 32Ch - 20x1MP + 12xD1 ; 64Ch - D1 |
| | Analytics | Camera Tampering, Line Crossing, Sterile Area, Object Monitoring |
| Audio | Input | 1CH + Depends on Camera Inputs |
| | Output | 1CH + Depends on Camera Outputs |
| | Two Way Audio | Yes |
| Bandwidth | Incoming | 320Mbps |
| | Outgoing | 320Mbps |
| Recording | Real-Time Recording | 64CH 8MP Real-Time |
| | 8MP | 1920FPS (NTSC)/1600FPS (PAL) |
| | 5MP | 1920FPS (NTSC)/1600FPS (PAL) |
| | 4MP | 1920FPS (NTSC)/1600FPS (PAL) |
| | 3MP | 1920FPS (NTSC)/1600FPS (PAL) |
| | 2MP (1080P) | 1920FPS (NTSC)/1600FPS (PAL) |
| | 1.3MP (960P) and lower | 1920FPS (NTSC)/1600FPS (PAL) |
| | Recording Modes | Schedule, Manual, Motion, Sensor, Analytics |
| Playback | Playback Channels | 16CH |
| | Search Mode | Time-Slice, Time, Event, File Management |
| Backup | USB | 2 USB 2.0 Port + 1 USB 3.0 Port |
| | DVD Burner | No |
| | Backup Format | AVI/DAT |
| Remote Application | Master Stream | Up to 64CH@Recording Resolution |
| | Sub-Stream | Depends on IPC |
| | Browser | Safari (Mac OS) IE (Windows Vista/7/8/10) |
| | CMS | Yes |
| | Mobile Application | Provision CAM2 for iOS/Android |
| | User Access | 10 Users Online with Professional Authority Management |
| Alarm | Input | 8CH + Depends on Camera |
| | Output | 4CH + Depends on Camera |
| Storage | HDD | 8 SATA (8TB Each) |
| | E-SATA | 2 |
| PTZ | Connection | Via Network |
| | Supported Controls | Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus |
| | RS-485 | No |
| Network | Ethernet | 2 x 1000 Mbps (2 x RJ-45) |
| | Protocol | TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP |
| | ONVIF | Yes |
| PoE | Ports | No |
| | Interface | No |
| | Standard | No |
| | Total Power | No |
| | Max. Power Output (Per Ch.) | No |
| Others | Power Supply | AC100-240V |
| | Power Consumption (No HDD) | 15W |
| | Dimension | W430xD445xH97mm |
| | Operation Temperature | 0°C ~50°C |