

# **IN05 & IN05-A**

# Fingerprint Recognition TA & Access Terminal



IN05 is a fingerprint identification time & attendance and access control terminal, which can connect with third party electric lock, door sensor and exit button etc.

Communicating via Wi-Fi, TCP/IP, 3G and USB host, it ensures a smooth connection and data transfer.

It's associated with ZK new fingerprint reader, the operation remains stable under strong light source and high preciseness of verification of wet and rough fingers. Amazing verification speed and intuitive Operation process make it popular. It will match your slap-up office perfectly.

#### **Features**



Build in PoE



1 channel auxiliary input for smoke detector connection



Build in battery, upto 4 hours



Multiple communicate mode, Wi-Fi, TCP/IP, 3G, USB host



Stable operation under strong light source




Advance access function including Lock connection, alarm, Wiegand input/output

### **Specifications**

Product		IN05	IN05-A	
Main	Biometric	Fingerprint		
	RF Optional	125kHz EM / 13.56MHz MF		
Capacity	Max User(1:N)	1,0000		
	Max Fingerprint (1:N)	3,000 standard / 10,000 Optional		
	Max Record	100,000		
Interface	TCP/IP	10/100 M		
	PoE Optional	802.3 at 28W		
	Wi-Fi	802.11 B/G/N		
	3G Optional	WCDMA		
	USB	USB 2.0 (Host)		
	RS232	1 port for external printer		
	RS485		1 port for FP reader	
	Relay	2 relays		
	Wiegand	1ch In & Out	1ch In & Out	
	Input		1 Input	
Hardware	LCD	2.8" Color LCD		
	Sound	24-bit		
	Operating Temp.	0 °C - 45 °C		
	Operating Humidity	20% ~ 80%		
	Power	DC 12V 1.5A	DC 12V 3A	
	Dimensions(W x H x D mm)	213*155*107.81mm		
	Certificates	CE, FCC, RoHS		
Function	Standard	Automatic Status Switch, Self-Service Query, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Lock, sensor, Exit button		
	Optiona	ID / MF, ADMS		
Compatibility		ZKTime.net 3.0, ZKTime	ZKTime.net 3.0, ZKTime.web 2.0, ZKTime 5.0, ZKAccess 3.5	
		1		

## Configuration



# Dimensions (mm)

