

Reolink-Go-IP-Camera-Specifications		
	Model	Reolink Go
Video & Audio	Image Sensor	Starlight CMOS Image Sensor
	Video Resolution	1080p HD at 15 frames/sec
	Video Format	H.264
	Field of View	Fixed lens, 110° diagonal
	Night Vision	Up to 10m (33ft)
	Digital Zoom	6x digital zoom
PIR Detection & Alerts	Audio	Speaker and microphone for two-way audio
	PIR Detecting Distance	Adjustable, up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Siren (customizable)
	Other Alerts	Instant email alerts and push notifications
3G/4G Bandwidth	Frequency Bands	Europe Version: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		America Version: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
	Transmission Data	Australia Version: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
Power	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Can be powered by Reolink Solar Panel
	DC Power	Can be powered by 5V/2A power adapter
Storage	Local Storage	Supports up to 64GB micro SD card
	Cloud Storage	Supports Reolink Cloud (available in some countries)
Working Environment	Operating Temperature	-10°C to 55°C (14°F to 131°F)
	Weather Resistance	IP65 certified weatherproof
Size & Weight	Size	Φ75 x 113 mm (Φ75 x 4.4 in)
	Weight (Battery included)	380 g (13.4 oz)
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .